

Surface wall luminaire with cutoff optics

Provides less than 2% uplight which meets LEED cutoff criteria for lighting zones LZ2, LZ3, and LZ4.

Housing: Constructed of copper free die cast aluminum alloy. The housing uses stainless steel inserts for enclosure attachment. Mounts over a standard 3½" or 4" octagonal wiring box.


Enclosure: LED luminaires have a clear tempered glass lens with a linear spread pattern. One piece, die cast, copper free, louvered, aluminum face plate secured to the housing with four captive socket head, stainless steel screws. Fully gasketed for water tight operation using a silicone rubber gasket.

Electrical: LED: 3 x 1W LEDs (3150K ± 200K). An internal driver is provided, rated for 120V through 255V. Like a traditional light source, the LED board is replaceable at the end of its life.

Finish: These luminaires are available in five standard BEGA colors: Black (BLK), White(WHT), Bronze (BRZ), Silver (SLV), Eurocoat™ (URO). To specify, add appropriate suffix to catalog number. Custom colors supplied on special order.

U.L. listed, suitable for wet locations. Protection class IP 65.

Type:
 BEGA Product #:
 Project:
 Voltage:
 Color:
 Options:
 Modified:



Wall mounted luminaires with cutoff optics. Anodized aluminum reflector. Linear spread glass lens. U.L. listed, suitable for wet location. IP 65. Color: Standard BEGA finishes.

Options

FSC Fusing



Lamp	Lumen	A	B	C
2228 3 x 1W LED		4¾	4¾	2¾